

BP818


Magnetic Coupler Isolator

Description

The BP818 is a magnetically coupled isolator designed for communication between primary and secondary of offline power supplies.

The BP818 has two built-in coupling coils and utilizes the magnetic coupling to , while providing galvanic isolation. The BP818 offers stable and reliable performance eliminating the disadvantages of traditional optocouplers such as low precision and nonlinear current transfer ratio, as well as limited lifetime. The BP818 operates without bias current on both the primary and secondary sides, which greatly reduces the system standby power consumption. In combination with the corresponding primary and secondary controllers of BPS, it can establish a high-performance switching power supply total solution.

The BP818 meets the global safety requirements for reinforced insulation. It utilizes an LSOP-4 package with a creepage distance of 8mm and isolation voltage up to 5000 VAC. Certified by UL62368, TUV (IEC62368), CQC (GB4943.1), VDE (IEC60747) for safety regulations.



LSOP-4 package

Feature

- Magnetic coupling with stable performance
- No lifetime decay
- Wide operating temperature: -55 °C ~ 125 °C
- No bias current required, reduces standby power consumption
- Up to 5000 VAC isolation voltage
- Creepage distance >8 mm
- UL62368 and TUV (IEC62368) certification
- CQC certification per GB4943.1-2022
- VDE (IEC60747) approved

Applications

- QC / USB PD / programable AC/DC chargers
- Adapters
- AC/DC auxiliary power

Electrical Schematic




Figure 1. Electrical Schematic

BPS Co

Disclaimer

The information provided in this datasheet is believed to be accurate and reliable. However, Bright Power Semiconductor (BPS) reserves the right to make changes at any time without prior notice.

No license, to any intellectual property right owned by BPS or any other third party, is granted under this document. BPS provides information in this datasheet AS IS and with all faults, and makes no warranty, express or implied, including but not limited to, the accuracy of the information provided in this datasheet, merchantability, fitness of a specific purpose, or non-infringement of intellectual property rights of BPS or any other third party. BPS disclaims any and all liabilities arising out of this datasheet or use of this datasheet, including without limitation consequential or incidental damages.